

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 August 2005 (25.08.2005)

PCT

(10) International Publication Number
WO 2005/077488 A1

(51) International Patent Classification⁷: **B01D 29/66**,
46/04, 35/16, 53/34

[CA/CA]; 67 - 11th Avenue, Roxboro, Québec H8Y 2P8
(CA).

(21) International Application Number:
PCT/CA2005/000190

(74) Agent: **OGILVY RENAULT**, Suite 1600, 1981 McGill
College Avenue, Montréal, Québec H3A 2Y3 (CA).

(22) International Filing Date: 14 February 2005 (14.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/543,926 13 February 2004 (13.02.2004) US

(71) Applicant (for all designated States except US): **PAT
TECHNOLOGY SYSTEMS INC.** [CA/CA]; 358
Joseph-Carrier, Vaudreuil-Dorion, Québec J7V 5V5 (CA).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(72) Inventor; and

(75) Inventor/Applicant (for US only): **VO, Chau, Thien**

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: **GAS FILTRATION SYSTEM AND FILTER CLEANING METHOD**



(57) Abstract: An apparatus (10, 200, 250, 250') for filtering particulates from a gas, comprising a casing (22, 24, 202) defining an inner cavity having an inlet (30, 210, 260) adapted to receive a flow of gas, such that gas enters the inner cavity, and an outlet (40, 231, 281) through which gas exits the inner cavity. A filter (32, 213, 262) is associated with the outlet (40, 231, 281) such that gas exiting the inner cavity through the outlet (40, 231, 281) passes through the filter (32, 213, 262). The filter (32, 213, 262) is adapted to retain particulates beyond a predetermined size from a gas flowing therethrough. A back-pulse generator (42, 223, 270) is positioned downstream of the filter (32, 213, 262). The back-pulse generator (42, 223, 270) is adapted to cause a reverse flow of gas through the outlet (40, 231, 281) and into the inner cavity of the casing, so as to dislodge a portion of the particulates retained in the filter (32, 213, 262) into the inner cavity.



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

— with amended claims

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report